



- NOTES:
- ELECTRICAL PROPERTIES:
    - 100% OPEN AND SHORT TEST
    - CONDUCTOR RESISTANCE: 5 OHMS
    - INSULATION RESISTANCE: 10 MEGOHMS
    - HI-POT: DC200V/0.01S
  - ALL MATERIAL BE RoHS COMPLIANT.

NO.	PARTS NAME	Q'TY	SPECIFICATION
⑨	TAG	1PCS	DELTACO TAG
⑧	CORE MOLD	2PCS	GRAY PVC
⑦	CORE	2PCS	OD*ID*L: 17.5*10.5*28.5mm
⑥	SCREW	2PCS	#4-40 UNC, 4*46mm HOOD MOLDED: BLUE PVC
⑤	HOOD MOLD	2PCS	BLUE PVC
④	INNER MOLD	2PCS	PE
③	HDB 15P F	1PCS	NICKIEL PLATED SHELL
②	HDB 15P M	1PCS	NICKIEL PLATED SHELL, UNLADAD 9PIN
①	CABLE	1PCS	(28AWG*1C+S+PVC)*3+24AWG*8C+AEB OD:9.0mm GRAY PVC JACKET

APPROVED	CHECKED	DRAWN	CUSTOMER:	
			ITEM NO.	RGB-6B
			DRAW NO.	
			UNIT	mm
			SCALE	NONE

DESCRIPTION:  
HDB 15/M-HDB 15/F  
(PIN 9 MISSING)

